

Perforated Release Film for Safety Glazing Vacuuming - High-Temp Vacuum Bag Film for PVB, SGP & EVA Laminated Glass

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Release film is made of FEP (perfluoroethylene propylene) and has a maximum temperature resistance of 260. It has good heat resistance, chemical resistance, and electrical insulation properties, is not easily adhered to other substances, and is easily peeled off. It is a very clean and smooth film, which has very good mechanical properties like even transparency, low thermal shrinkage, good tensile strength and good mold release. It is widely used in the vacuum infusion.

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Type	Material	Color	Thickness	Max Temp.	Operating	Width	Tensile strength	Elongation at break
Non-perforated	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%
Perforated (as per customer requirement)	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%



Peter Lin  
[cnc@cncGlass.com](mailto:cnc@cncGlass.com)  
 Whatsapp: +86 15013829504  
 WeChat: wecan365  
 Mobile: +86 15013829504  
[www.cncglass.com](http://www.cncglass.com)

please feel free to contact us!  
 the best to our clients!

Perforated Release Film for Safety Glazing Vacuuming - High-Temp Vacuum Bag Film for PVB, SGP & EVA Laminated Glass

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Release film is made of FEP (perfluoroethylene propylene) and has a maximum temperature resistance of 260. It has good heat resistance, chemical resistance, and electrical insulation properties, is not easily adhered to other substances, and is easily peeled off. It is a very clean and smooth film, which has very good mechanical properties like even transparency, low thermal shrinkage, good tensile strength and good mold release. It is widely used in the vacuum infusion.

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Type	Material	Color	Thickness	Max Temp.	Operating	Width	Tensile strength	Elongation at break
Non-perforated	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%
Perforated (as per customer requirement)	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%



Peter Lin  
 cnc@cncGlass.com  
 Whatsapp: +86 15013829504  
 WeChat: wecan365  
 Mobile: +86 15013829504  
 www.cncglass.com

Perforated Release Film for Safety Glazing Vacuuming - High-Temp Vacuum Bag Film for PVB, SGP & EVA Laminated Glass

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Release film is made of FEP (perfluoroethylene propylene) and has a maximum temperature resistance of 260. It has good heat resistance, chemical resistance, and electrical insulation properties, is not easily adhered to other substances, and is easily peeled off. It is a very clean and smooth film, which has very good mechanical properties like even transparency, low thermal shrinkage, good tensile strength and good mold release. It is widely used in the vacuum infusion.

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Type	Material	Color	Thickness	Max Temp.	Operating	Width	Tensile strength	Elongation at break
Non-perforated	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%
Perforated (as per customer requirement)	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%



Peter Lin  
 cnc@cncGlass.com  
 Whatsapp: +86 15013829504  
 WeChat: wecan365  
 Mobile: +86 15013829504  
 www.cncglass.com

Perforated Release Film for Safety Glazing Vacuuming - High-Temp Vacuum Bag Film for PVB, SGP & EVA Laminated Glass

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Release film is made of FEP (perfluoroethylene propylene) and has a maximum temperature resistance of 260. It has good heat resistance, chemical resistance, and electrical insulation properties, is not easily adhered to other substances, and is easily peeled off. It is a very clean and smooth film, which has very good mechanical properties like even transparency, low thermal shrinkage, good tensile strength and good mold release. It is widely used in the vacuum infusion.

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Type	Material	Color	Thickness	Max Temp.	Operating	Width	Tensile strength	Elongation at break
Non-perforated	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%
Perforated (as per customer requirement)	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%



Peter Lin  
 cnc@cncGlass.com  
 Whatsapp: +86 15013829504  
 WeChat: wecan365  
 Mobile: +86 15013829504  
 www.cncglass.com

Perforated Release Film for Safety Glazing Vacuuming - High-Temp Vacuum Bag Film for PVB, SGP & EVA Laminated Glass

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Release film is made of FEP (perfluoroethylene propylene) and has a maximum temperature resistance of 260. It has good heat resistance, chemical resistance, and electrical insulation properties, is not easily adhered to other substances, and is easily peeled off. It is a very clean and smooth film, which has very good mechanical properties like even transparency, low thermal shrinkage, good tensile strength and good mold release. It is widely used in the vacuum infusion.

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Type	Material	Color	Thickness	Max Temp.	Operating	Width	Tensile strength	Elongation at break
Non-perforated	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%
Perforated (as per customer requirement)	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%



Peter Lin  
[cnc@cncGlass.com](mailto:cnc@cncGlass.com)  
 Whatsapp: +86 15013829504  
 WeChat: wecan365  
 Mobile: +86 15013829504  
[www.cncglass.com](http://www.cncglass.com)

Perforated Release Film for Safety Glazing Vacuuming - High-Temp Vacuum Bag Film for PVB, SGP & EVA Laminated Glass

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Release film is made of FEP (perfluoroethylene propylene) and has a maximum temperature resistance of 260. It has good heat resistance, chemical resistance, and electrical insulation properties, is not easily adhered to other substances, and is easily peeled off. It is a very clean and smooth film, which has very good mechanical properties like even transparency, low thermal shrinkage, good tensile strength and good mold release. It is widely used in the vacuum infusion.

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Type	Material	Color	Thickness	Max Temp.	Operating	Width	Tensile strength	Elongation at break
Non-perforated	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%
Perforated (as per customer requirement)	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%



Peter Lin  
[cnc@cncGlass.com](mailto:cnc@cncGlass.com)  
 Whatsapp: +86 15013829504  
 WeChat: wecan365  
 Mobile: +86 15013829504  
[www.cncglass.com](http://www.cncglass.com)

Perforated Release Film for Safety Glazing Vacuuming - High-Temp Vacuum Bag Film for PVB, SGP & EVA Laminated Glass

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Release film is made of FEP (perfluoroethylene propylene) and has a maximum temperature resistance of 260. It has good heat resistance, chemical resistance, and electrical insulation properties, is not easily adhered to other substances, and is easily peeled off. It is a very clean and smooth film, which has very good mechanical properties like even transparency, low thermal shrinkage, good tensile strength and good mold release. It is widely used in the vacuum infusion.

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Type	Material	Color	Thickness	Max Temp.	Operating	Width	Tensile strength	Elongation at break
Non-perforated	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%
Perforated (as per customer requirement)	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%



Peter Lin  
[cnc@cncGlass.com](mailto:cnc@cncGlass.com)  
 Whatsapp: +86 15013829504  
 WeChat: wecan365  
 Mobile: +86 15013829504  
[www.cncglass.com](http://www.cncglass.com)

Perforated Release Film for Safety Glazing Vacuuming - High-Temp Vacuum Bag Film for PVB, SGP & EVA Laminated Glass

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Release film is made of FEP (perfluoroethylene propylene) and has a maximum temperature resistance of 260. It has good heat resistance, chemical resistance, and electrical insulation properties, is not easily adhered to other substances, and is easily peeled off. It is a very clean and smooth film, which has very good mechanical properties like even transparency, low thermal shrinkage, good tensile strength and good mold release. It is widely used in the vacuum infusion.

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Type	Material	Color	Thickness	Max Temp.	Operating	Width	Tensile strength	Elongation at break
Non-perforated	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%
Perforated (as per customer requirement)	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%



Peter Lin  
[cnc@cncGlass.com](mailto:cnc@cncGlass.com)  
 Whatsapp: +86 15013829504  
 WeChat: wecan365  
 Mobile: +86 15013829504  
[www.cncglass.com](http://www.cncglass.com)

Perforated Release Film for Safety Glazing Vacuuming - High-Temp Vacuum Bag Film for PVB, SGP & EVA Laminated Glass

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Release film is made of FEP (perfluoroethylene propylene) and has a maximum temperature resistance of 260. It has good heat resistance, chemical resistance, and electrical insulation properties, is not easily adhered to other substances, and is easily peeled off. It is a very clean and smooth film, which has very good mechanical properties like even transparency, low thermal shrinkage, good tensile strength and good mold release. It is widely used in the vacuum infusion.

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Type	Material	Color	Thickness	Max Temp.	Operating	Width	Tensile strength	Elongation at break
Non-perforated	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%
Perforated (as per customer requirement)	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%



Peter Lin  
 cnc@cncGlass.com  
 Whatsapp: +86 15013829504  
 WeChat: wecan365  
 Mobile: +86 15013829504  
 www.cncglass.com

Perforated Release Film for Safety Glazing Vacuuming - High-Temp Vacuum Bag Film for PVB, SGP & EVA Laminated Glass

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Release film is made of FEP (perfluoroethylene propylene) and has a maximum temperature resistance of 260. It has good heat resistance, chemical resistance, and electrical insulation properties, is not easily adhered to other substances, and is easily peeled off. It is a very clean and smooth film, which has very good mechanical properties like even transparency, low thermal shrinkage, good tensile strength and good mold release. It is widely used in the vacuum infusion.

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Type	Material	Color	Thickness	Max Temp.	Operating	Width	Tensile strength	Elongation at break
Non-perforated	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%
Perforated (as per customer requirement)	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%



Peter Lin  
[cnc@cncGlass.com](mailto:cnc@cncGlass.com)  
 Whatsapp: +86 15013829504  
 WeChat: wecan365  
 Mobile: +86 15013829504  
[www.cncglass.com](http://www.cncglass.com)

Perforated Release Film for Safety Glazing Vacuuming - High-Temp Vacuum Bag Film for PVB, SGP & EVA Laminated Glass

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Release film is made of FEP (perfluoroethylene propylene) and has a maximum temperature resistance of 260. It has good heat resistance, chemical resistance, and electrical insulation properties, is not easily adhered to other substances, and is easily peeled off. It is a very clean and smooth film, which has very good mechanical properties like even transparency, low thermal shrinkage, good tensile strength and good mold release. It is widely used in the vacuum infusion.

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Type	Material	Color	Thickness	Max Temp.	Operating	Width	Tensile strength	Elongation at break
Non-perforated	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%
Perforated (as per customer requirement)	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%



Peter Lin  
 cnc@cncGlass.com  
 Whatsapp: +86 15013829504  
 WeChat: wecan365  
 Mobile: +86 15013829504  
 www.cncglass.com

Perforated Release Film for Safety Glazing Vacuuming - High-Temp Vacuum Bag Film for PVB, SGP & EVA Laminated Glass

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Release film is made of FEP (perfluoroethylene propylene) and has a maximum temperature resistance of 260. It has good heat resistance, chemical resistance, and electrical insulation properties, is not easily adhered to other substances, and is easily peeled off. It is a very clean and smooth film, which has very good mechanical properties like even transparency, low thermal shrinkage, good tensile strength and good mold release. It is widely used in the vacuum infusion.

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Type	Material	Color	Thickness	Max Temp.	Operating	Width	Tensile strength	Elongation at break
Non-perforated	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%
Perforated (as per customer requirement)	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%



Peter Lin  
[cnc@cncGlass.com](mailto:cnc@cncGlass.com)  
 Whatsapp: +86 15013829504  
 WeChat: wecan365  
 Mobile: +86 15013829504  
[www.cncglass.com](http://www.cncglass.com)

Perforated Release Film for Safety Glazing Vacuuming - High-Temp Vacuum Bag Film for PVB, SGP & EVA Laminated Glass

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Release film is made of FEP (perfluoroethylene propylene) and has a maximum temperature resistance of 260. It has good heat resistance, chemical resistance, and electrical insulation properties, is not easily adhered to other substances, and is easily peeled off. It is a very clean and smooth film, which has very good mechanical properties like even transparency, low thermal shrinkage, good tensile strength and good mold release. It is widely used in the vacuum infusion.

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Type	Material	Color	Thickness	Max Temp.	Operating	Width	Tensile strength	Elongation at break
Non-perforated	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%
Perforated (as per customer requirement)	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%



Peter Lin  
[cnc@cncGlass.com](mailto:cnc@cncGlass.com)  
 Whatsapp: +86 15013829504  
 WeChat: wecan365  
 Mobile: +86 15013829504  
[www.cncglass.com](http://www.cncglass.com)

Perforated Release Film for Safety Glazing Vacuuming - High-Temp Vacuum Bag Film for PVB, SGP & EVA Laminated Glass

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Release film is made of FEP (perfluoroethylene propylene) and has a maximum temperature resistance of 260. It has good heat resistance, chemical resistance, and electrical insulation properties, is not easily adhered to other substances, and is easily peeled off. It is a very clean and smooth film, which has very good mechanical properties like even transparency, low thermal shrinkage, good tensile strength and good mold release. It is widely used in the vacuum infusion.

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Type	Material	Color	Thickness	Max Temp.	Operating	Width	Tensile strength	Elongation at break
Non-perforated	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%
Perforated (as per customer requirement)	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%



Peter Lin  
[cnc@cncGlass.com](mailto:cnc@cncGlass.com)  
 Whatsapp: +86 15013829504  
 WeChat: wecan365  
 Mobile: +86 15013829504  
[www.cncglass.com](http://www.cncglass.com)

Perforated Release Film for Safety Glazing Vacuuming - High-Temp Vacuum Bag Film for PVB, SGP & EVA Laminated Glass

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Release film is made of FEP (perfluoroethylene propylene) and has a maximum temperature resistance of 260. It has good heat resistance, chemical resistance, and electrical insulation properties, is not easily adhered to other substances, and is easily peeled off. It is a very clean and smooth film, which has very good mechanical properties like even transparency, low thermal shrinkage, good tensile strength and good mold release. It is widely used in the vacuum infusion.

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Type	Material	Color	Thickness	Max Temp.	Operating	Width	Tensile strength	Elongation at break
Non-perforated	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%
Perforated (as per customer requirement)	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%



Peter Lin  
[cnc@cncGlass.com](mailto:cnc@cncGlass.com)  
 Whatsapp: +86 15013829504  
 WeChat: wecan365  
 Mobile: +86 15013829504  
[www.cncglass.com](http://www.cncglass.com)

Perforated Release Film for Safety Glazing Vacuuming - High-Temp Vacuum Bag Film for PVB, SGP & EVA Laminated Glass

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Release film is made of FEP (perfluoroethylene propylene) and has a maximum temperature resistance of 260. It has good heat resistance, chemical resistance, and electrical insulation properties, is not easily adhered to other substances, and is easily peeled off. It is a very clean and smooth film, which has very good mechanical properties like even transparency, low thermal shrinkage, good tensile strength and good mold release. It is widely used in the vacuum infusion.

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Type	Material	Color	Thickness	Max Temp.	Operating	Width	Tensile strength	Elongation at break
Non-perforated	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%
Perforated (as per customer requirement)	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%



Peter Lin  
[cnc@cncGlass.com](mailto:cnc@cncGlass.com)  
 Whatsapp: +86 15013829504  
 WeChat: wecan365  
 Mobile: +86 15013829504  
[www.cncglass.com](http://www.cncglass.com)

Perforated Release Film for Safety Glazing Vacuuming - High-Temp Vacuum Bag Film for PVB, SGP & EVA Laminated Glass

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Release film is made of FEP (perfluoroethylene propylene) and has a maximum temperature resistance of 260. It has good heat resistance, chemical resistance, and electrical insulation properties, is not easily adhered to other substances, and is easily peeled off. It is a very clean and smooth film, which has very good mechanical properties like even transparency, low thermal shrinkage, good tensile strength and good mold release. It is widely used in the vacuum infusion.

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Type	Material	Color	Thickness	Max Temp.	Operating	Width	Tensile strength	Elongation at break
Non-perforated	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%
Perforated (as per customer requirement)	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%



Peter Lin  
[cnc@cncGlass.com](mailto:cnc@cncGlass.com)  
 Whatsapp: +86 15013829504  
 WeChat: wecan365  
 Mobile: +86 15013829504  
[www.cncglass.com](http://www.cncglass.com)

Perforated Release Film for Safety Glazing Vacuuming - High-Temp Vacuum Bag Film for PVB, SGP & EVA Laminated Glass

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Release film is made of FEP (perfluoroethylene propylene) and has a maximum temperature resistance of 260. It has good heat resistance, chemical resistance, and electrical insulation properties, is not easily adhered to other substances, and is easily peeled off. It is a very clean and smooth film, which has very good mechanical properties like even transparency, low thermal shrinkage, good tensile strength and good mold release. It is widely used in the vacuum infusion.

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Type	Material	Color	Thickness	Max Temp.	Operating	Width	Tensile strength	Elongation at break
Non-perforated	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%
Perforated (as per customer requirement)	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%



Peter Lin  
[cnc@cncGlass.com](mailto:cnc@cncGlass.com)  
 Whatsapp: +86 15013829504  
 WeChat: wecan365  
 Mobile: +86 15013829504  
[www.cncglass.com](http://www.cncglass.com)

Perforated Release Film for Safety Glazing Vacuuming - High-Temp Vacuum Bag Film for PVB, SGP & EVA Laminated Glass

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Release film is made of FEP (perfluoroethylene propylene) and has a maximum temperature resistance of 260. It has good heat resistance, chemical resistance, and electrical insulation properties, is not easily adhered to other substances, and is easily peeled off. It is a very clean and smooth film, which has very good mechanical properties like even transparency, low thermal shrinkage, good tensile strength and good mold release. It is widely used in the vacuum infusion.

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Type	Material	Color	Thickness	Max Temp.	Operating	Width	Tensile strength	Elongation at break
Non-perforated	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%
Perforated (as per customer requirement)	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%



Peter Lin  
[cnc@cncGlass.com](mailto:cnc@cncGlass.com)  
 Whatsapp: +86 15013829504  
 WeChat: wecan365  
 Mobile: +86 15013829504  
[www.cncglass.com](http://www.cncglass.com)

Perforated Release Film for Safety Glazing Vacuuming - High-Temp Vacuum Bag Film for PVB, SGP & EVA Laminated Glass

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Release film is made of FEP (perfluoroethylene propylene) and has a maximum temperature resistance of 260. It has good heat resistance, chemical resistance, and electrical insulation properties, is not easily adhered to other substances, and is easily peeled off. It is a very clean and smooth film, which has very good mechanical properties like even transparency, low thermal shrinkage, good tensile strength and good mold release. It is widely used in the vacuum infusion.

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Type	Material	Color	Thickness	Max Temp.	Operating	Width	Tensile strength	Elongation at break
Non-perforated	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%
Perforated (as per customer requirement)	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%



Peter Lin  
 cnc@cncGlass.com  
 Whatsapp: +86 15013829504  
 WeChat: wecan365  
 Mobile: +86 15013829504  
 www.cncglass.com

Perforated Release Film for Safety Glazing Vacuuming - High-Temp Vacuum Bag Film for PVB, SGP & EVA Laminated Glass

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Release film is made of FEP (perfluoroethylene propylene) and has a maximum temperature resistance of 260. It has good heat resistance, chemical resistance, and electrical insulation properties, is not easily adhered to other substances, and is easily peeled off. It is a very clean and smooth film, which has very good mechanical properties like even transparency, low thermal shrinkage, good tensile strength and good mold release. It is widely used in the vacuum infusion.

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Type	Material	Color	Thickness	Max Temp.	Operating	Width	Tensile strength	Elongation at break
Non-perforated	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%
Perforated (as per customer requirement)	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%



Peter Lin  
[cnc@cncGlass.com](mailto:cnc@cncGlass.com)  
 Whatsapp: +86 15013829504  
 WeChat: wecan365  
 Mobile: +86 15013829504  
[www.cncglass.com](http://www.cncglass.com)

Perforated Release Film for Safety Glazing Vacuuming - High-Temp Vacuum Bag Film for PVB, SGP & EVA Laminated Glass

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Release film is made of FEP (perfluoroethylene propylene) and has a maximum temperature resistance of 260. It has good heat resistance, chemical resistance, and electrical insulation properties, is not easily adhered to other substances, and is easily peeled off. It is a very clean and smooth film, which has very good mechanical properties like even transparency, low thermal shrinkage, good tensile strength and good mold release. It is widely used in the vacuum infusion.

[cnc@cncglass.com](mailto:cnc@cncglass.com)

Type	Material	Color	Thickness	Max Temp.	Operating	Width	Tensile strength	Elongation at break
Non-perforated	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%
Perforated (as per customer requirement)	FEP	Red	20 ± 5 μm	260° C		≤ 1.5 m	21Mpa	300%



Peter Lin  
 cnc@cncGlass.com  
 Whatsapp: +86 15013829504  
 WeChat: wecan365  
 Mobile: +86 15013829504  
 www.cncglass.com